

Safety Data Sheet

WABO PASTE ADHESIVE WARM WEATHER PART A

Revision date : 2010/04/21

Page: 1/6

Version: 1.0

(298891/SDS_GEN_US/EN)

1. Product and Company Identification

Company

Watson Bowman Acme Corporation
95 Pineview Drive
Amherst, NY 14228 USA

24 Hour Emergency Response Information

CHEMTREC: 1-800-424-9300
BASF HOTLINE: 1-800-832-HELP

2. Hazards Identification

Emergency overview

WARNING:

MAY CAUSE ALLERGIC SKIN REACTION.

MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION.

CONTAINS MATERIAL WHICH MAY CAUSE CANCER.

Ingestion may cause irritation to mucous membranes.

Avoid contact with the skin, eyes and clothing.

Wash thoroughly after handling.

Keep container tightly closed.

No exposure to respirable Crystalline (quartz) Silica anticipated with recommended use of product.

State of matter: solid

Colour: light grey

Odour: sweetish

Potential health effects**Primary routes of exposure:**

Routes of entry for solids and liquids include eye and skin contact, ingestion and inhalation. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquified gases.

Irritation / corrosion:

Prolonged contact with the product can result in skin irritation. May cause slight irritation to the eyes.

Sensitization:

May cause allergic skin reaction.

Potential environmental effects**Aquatic toxicity:**

No data available concerning aquatic toxicity.

Safety Data Sheet

WABO PASTE ADHESIVE WARM WEATHER PART A

Revision date : 2010/04/21
Version: 1.0

Page: 2/6
(298891/SDS_GEN_US/EN)

3. Composition / Information on Ingredients

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
14808-60-7	>= 40.0 - <= 70.0 %	crystalline silica
25068-38-6	>= 15.0 - <= 40.0 %	bisphenol A-epichlorohydrin resin
2210-79-9	>= 7.0 - <= 13.0 %	Oxirane, 2-[(2-methylphenoxy)methyl]-

4. First-Aid Measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth immediately with water. Seek medical attention if necessary. Do not induce vomiting unless told to by a poison control center or doctor.

5. Fire-Fighting Measures

Flash point: 201 °F
94 °C

Suitable extinguishing media:

carbon dioxide, dry extinguishing media, foam, water fog, water spray

Hazards during fire-fighting:

carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions:

Use personal protective clothing. Avoid contact with the skin, eyes and clothing. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Cleanup:

For small amounts: Sweep/shovel up. Dispose of absorbed material in accordance with regulations.
For large amounts: Sweep/shovel up. Dispose of absorbed material in accordance with regulations.

Safety Data Sheet

WABO PASTE ADHESIVE WARM WEATHER PART A

Revision date : 2010/04/21
Version: 1.0

Page: 3/6
(298891/SDS_GEN_US/EN)

7. Handling and Storage

Handling

General advice:

Avoid contact with the skin, eyes and clothing.

Protection against fire and explosion:

The substance/product is non-combustible. The product does not contribute to the spreading of flames, nor is it self combustible, not explosive.

Storage

General advice:

Keep only in the original container in a cool, well-ventilated place. Protect from direct sunlight. Store protected against freezing.

8. Exposure Controls and Personal Protection

Components with workplace control parameters

crystalline silica	OSHA	TWA value 2.4 millions of particles per cubic foot of air Respirable ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation. TWA value 0.1 mg/m3 Respirable ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation. TWA value 0.3 mg/m3 Total dust ; The value is calculated from a specified equation using a value of 100%. Lower values of % will give higher exposure limits. See regulation for specific equation.
	ACGIH	TWA value 0.025 mg/m3 Respirable fraction ;

Personal protective equipment

Hand protection:

Wear chemical resistant protective gloves.

Eye protection:

Safety glasses with side-shields.

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form:	paste	
Odour:	sweetish	
Colour:	light grey	
pH value:		not applicable
Melting point:		not applicable
Density:	1.76 g/cm3	

Safety Data Sheet

WABO PASTE ADHESIVE WARM WEATHER PART A

Revision date : 2010/04/21
Version: 1.0

Page: 4/6
(298891/SDS_GEN_US/EN)

Partitioning coefficient n-octanol/water (log Pow): not applicable

10. Stability and Reactivity

Conditions to avoid:

See MSDS section 7 - Handling and storage.

Substances to avoid:

strong acids, strong bases, strong oxidizing agents

Hazardous reactions:

The product is stable if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

Oxidizing properties:

Not an oxidizer.

11. Toxicological information

Irritation / corrosion

Information on: bisphenol A-epichlorohydrin resin

Assessment of irritating effects:

Eye contact causes irritation. Skin contact causes irritation.

Information on: Oxirane, 2-[(2-methylphenoxy)methyl]-

Assessment of irritating effects:

Eye contact causes irritation. Skin contact causes irritation.

Sensitization

Information on: bisphenol A-epichlorohydrin resin

Assessment of sensitization:

Sensitization after skin contact possible.

Information on: Oxirane, 2-[(2-methylphenoxy)methyl]-

Assessment of sensitization:

Caused skin sensitization in animal studies.

Carcinogenicity

Information on: crystalline silica

The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.

Experiences in humans:

According to experience, the product is considered to be harmless to health if used in the correct manner.

Other Information:

The product has not been tested. The statement has been derived from the properties of the individual components.

Safety Data Sheet

WABO PASTE ADHESIVE WARM WEATHER PART A

Revision date : 2010/04/21
Version: 1.0

Page: 5/6
(298891/SDS_GEN_US/EN)

12. Ecological Information

Other adverse effects:

Do not allow to enter soil, waterways or waste water channels. According to experience, the material has no harmful effect on the environment.

13. Disposal considerations

Waste disposal of substance:

Observe national and local legal requirements. Residues should be disposed of in the same manner as the substance/product.

14. Transport Information

Land transport
USDOT

Not classified as a dangerous good under transport regulations

Sea transport
IMDG

Not classified as a dangerous good under transport regulations

Air transport
IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released / listed

OSHA hazard category:

IARC 1, 2A or 2B carcinogen; NTP listed carcinogen; Chronic target organ effects reported; OSHA PEL established; ACGIH TLV established

EPCRA 311/312 (Hazard categories):

Acute; Chronic

State regulations

State RTK
MA, NJ, PA

CAS Number
14808-60-7

Chemical name
crystalline silica

CA Prop. 65:

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER.

Safety Data Sheet

WABO PASTE ADHESIVE WARM WEATHER PART A

Revision date : 2010/04/21

Version: 1.0

Page: 6/6

(298891/SDS_GEN_US/EN)

16. Other Information

HMIS III rating

Health: 2 Flammability: 1 Physical hazard: 0

NFPA and HMIS use a numbering scale ranging from 0 to 4 to indicate the degree of hazard. A value of zero means that the substance possesses essentially no hazard; a rating of four indicates extreme danger. Although similar, the two rating systems are intended for different purposes, and use different criteria. The NFPA system was developed to provide an on-the-spot alert to the hazards of a material, and their severity, to emergency responders. The HMIS system was designed to communicate workplace hazard information to employees who handle hazardous chemicals.

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

MSDS Prepared by:

BASF NA Product Regulations

msds@basf.com

MSDS Prepared on: 2010/04/21

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY BASF HEREUNDER ARE GIVEN GRATIS AND BASF ASSUMES NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.
END OF DATA SHEET